

RF ADMITTANCE LEVEL SENSOR


The RF Admittance type level switch is a simple, low cost, rugged point Level Switch designed for Level detection of Bulk materials in a bin or silo. This level switch can be used for detecting high, low level or for differential level control and is used in cement industries, material handling plants, chemical industry, power utilities industry, food industry, pulp/paper industry, pharmaceuticals industry, water / waste industry, foundry industry etc.

The specialty of the probe is that it tends to ignore the build-up on the probe, thus making it suitable for application, which tends to stick on the probe.

The unit has integral electronics along with time delay feature, LED indication, fail safe mode etc.



Probe Construction suitable for material built up:



Normal probe tends to fail when there is a build-up on the probe. The COAT Guard electrode senses the material build up on the probe by employing a special Build up sensing technology. The COAT guard unit is insulated from the active probe and the ground is driven with same RF frequency as that of active electrode and having the same polarity. When a material build up is formed on the probe, the RF current from the COAT guard unit tends to saturate the build-up area between COAT guard probe and silo wall, thereby no electrical energy will flow from active probe to tank wall. When the material level goes up and touches the sense probe a RF current will flow from the sense probe to ground over and above the saturated region formed by the Built up sensing circuitry.

RF ADMITTANCE LEVEL SENSOR

SALIENT FEATURES

- Wide range of application
- Easy installation and maintenance.
- Weatherproof/Flameproof enclosure as per requirement
- Sturdy electrode to withstand impact due to accidental clinker formation
- Ceramic insulated electrode capable of withstanding 450°C
- No moving parts, no mechanical wear and tear.
- Adjustable differential time delay with ON/OFF timing.
- Fail Safe High/Low Selection Feature (Field configurable) Available
- Ignores Build Up of Sticky and Conductive Material between Probe and Vessel Walls

SPECIFICATIONS

	MODEL NUMBER
SUPPLY VOLTAGE	230VAC or 110VAC or 24V DC (factory selectable) 1
OUTPUT TYPE	DPDT Relay
CONTACT RATING	05 AMPS at 230VAC /24VDC, Resistive load Dual,
CABLE ENTRY	"PG 16, etc.
TEMPERATURE	0-100°C for integral type. 0-250°C for integral with Standoff, type 0-450°C for Remote with Standoff, type Type:
PROBE	Rigid Probe with Coat guard electrode Insulation: Teflon/Ceramic (for high temperature) Probe
MATERIALS	Length: As per requirement, Housing: Cast Al. Probes (Sense & Shield SS316/SS304), Flange/Adapter: SS316/SS304/C.S. Flanged or threaded process connection as per requirement. Weatherproof as per IP 66
MOUNTING	Flameproof (optional)
FREQUENCY	110 KHz
TIME DELAY	0 To 30 seconds adjustable With ON/OFF delay
FAIL SAFE	Selection Selectable.

INFORMATION REQUIRED Before Purchase

- Process Parameters: Temperature, pressure, atmosphere hazardous or not.
- Application media characteristics: Sp. Gr., Dielectric constant, hazardous or not, corrosiveness, viscosity.

Manufactured By:

[Arihant Instruments](#)